

InfernoMP10E SET UP SHEET

ver.1.00

KYOSHO
THE BEST RACING CONTROL MODELS

Driver		Date	Track	Event	Spur Gear	Pinion Gear
			Condition :		☒ 46T(Std.) ☐ 47T ☐ 48T	T
Motor	Battery	ESC	Tires	Tire Insert	Wheel	Body
			Compound :			

● Diff. Gear Set-Up

	Front	Center	Rear
Diff. Gear	☒ Std. ☐ LSD ☐ IFW621	☒ Std. ☐ LSD ☐ IFW622	☒ Std. ☐ LSD ☐ IFW621
	Ring Gear ☐ 43/13 ☐ 42/12		Ring Gear ☐ 43/13 ☐ 42/12
	# 4000	# 6000	# 3000

● Shock Set-Up

	Front	Rear
Shock Type	P : w/Diaphragm A : Aeration	
Shock Piston	B : Black W : White T : Taper	
Shock Oil	# 550	# 450
Shock Spring	Length 70 Color Red	Length 81 Color Light Purple

● Ride Height

Front	Rear
26 mm	28 mm

● Rebound

Front	Rear
102 mm	118 mm

● Camber Angle

Front	Rear
+ 1 °	+ 2 °


● Toe Angle

Front	Rear
+ °	☐ 2.5° ☒ 3° ☐ 3.5°

● Wheelbase

Collar of Rear Hub	Front Side	Rear Side
	3 mm	2 mm

● Shock Mount Position



Shock Stay

Front	Std.	Long
Rear	Std.	Long


Rear Upper Shock Bush

Std.	Long
------	------

Sus. Arm

Front	In	Out
Rear	In	Out

● Rear Upper Arm Position



Plastic	Aluminum
---------	----------

Hub Carrier Bush	Plastic	Brass
------------------	---------	-------

● Rear Wheel Hub

Narrow	Std.	Wide
--------	------	------


● Front Sus. Arm

Soft (Std.)	Hard
-------------	------

● Front Sus. Bush

Rear Side	
-----------	--

● Front Upper Arm Position




● Front Wheel Hub

Narrow	Std.	Wide
--------	------	------

● Front Hub Carrier

☒ Plastic	☐ Aluminum		
☐ 13°	☐ 16°	☒ 17.5°	☐ 19°



● Lower Bush

 -1° 	 0° 	 +1° 
---	--	---

● Rear Sus. Bush

Front Side	
Rear Side	

● Rear Sus. Arm

Soft (Std.)	Hard
-------------	------


Rear Sus. Bush

Short	Medium	Long
-------	--------	------


● Servo Horn

Steering	Throttle
☒ Plastic ☐ AL. Long ☐ AL. Short	☐ Plastic ☐ AL.

● Steering Plate



● Sway Bar



Front	Rear
φ 2.4	φ 2.7
0 mm	0 mm

● Weight

Front	Rear
☒ None ☐ IFW604-10 ☐ IFW604-20 ☐ other	☒ None ☐ IFW605-10 ☐ IFW605-20 ☐ other

● Wing

IF491(TK14)	Flap	None
	5mm	
	8mm	
	Holes	

memo: